

## **Glass Specs**

**Flushglaze** - 28mm DGU – 6mm Toughened Outer, 16mm Air Filled Cavity, 6mm toughened Soft Coat Low E inner

**Visionvent** - 32mm DGU – 6mm Toughened Outer, 20mm Air Filled Cavity, 6mm toughened Soft Coat Low E inner

**Walk On Flushglaze** – 43.5mm DGU – 21.5mm Clear Toughened Laminated Heat Soaked Outer, 16 Air Filled Cavity, 6mm toughened Soft Coat Low E inner

**Triple Glazed Flushglaze** – 46mm DGU – 6mm Clear Toughened Outer Pane, 12mm Air Filled Cavity, 6mm Soft Low E centre pane, 16mm Air filled cavity, 6mm Clear toughened inner pane

**Fire Rated Flushglaze** – 6mm Clear Toughened Low E Outer Pane – 20mm Steel Spacer bar – 19mm Laminated Fire Rated Inner Pane

**Flushglaze with Suncool** – 28mm DGU – Suncool 66/33 Brilliant Toughened Outer – 16mm Argon Filled Cavity – 6mm Clear Toughened Inner

**Flushglaze with Coolite** – 28mm DGU – Coolite SKN174 Neutral Toughened Outer - 16mm Argon Filled Cavity – 6mm Clear Toughened Inner

**Visionvent with Suncool** - 32mm DGU – Suncool 66/33 Brilliant Toughened Outer – 20mm Argon Filled Cavity – 6mm Clear Toughened Inner

**Flushglaze with Argon** - 28mm DGU – 6mm Toughened Outer, 16mm Argon Filled Cavity, 6mm toughened Soft Coat Low E inner

**Flushglaze with Laminate** – 28.8mm DGU – 6mm Toughened Outer, 14mm Argon Filled Cavity, 8.8mm Laminated Soft Coat Low E inner

**Visionvent with Argon** - 32mm DGU – 6mm Toughened Outer, 20mm Argon Filled Cavity, 6mm toughened Soft Coat Low E inner

**Visionvent with Laminate**- 32.8mm DGU – 6mm Toughened Outer, 18mm Air Filled Cavity, 8.8mm Laminated Soft Coat Low E inner